


1100 PROFILE

1000 Series



Cross-section dimensions:



THE THINNEST OF THE 1000 SERIES

This profile is **the thinnest of the 1000 Series** being only 6 mm (0.236 inch) thick and 18.7 mm (0.736 inch) wide, and is compatible with most of our LED engines. Perfect for tight spots, it will be very discreet and will stand out.

FEATURES

- The most compact profile of the 1000 Series, only 6mm thick.
- Custom length by sections of 2 to 240 inches (6m).
- Application guide for 10mm (3/8 inch) LED engine or less.
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Compatible with multiple installation accessories.
- Designed to meet North American woodworking standards.

OPTIONS



LED ENGINE COMPATIBILITY

Compatible with LED engines up to **14mm** wide.

LINEAR WEIGHT

0.060 lbs/ft, 0.089 kg/m (without lens)




















*Dot free only in certain configurations - contact your sales representatives for information



Profile ordering sheet

1000 Series

1000

PROFILE	LENSES	MOUNTING HARDWARE	LENGTH
 1100 - 1100 Profile, alu	 CL - Clear lens	 FL - Flat bracket	Custom length by sections of 2 to 240 inches (6m).
 1101 - 1100 Profile, black	 SP - Spread lens	 45 - 45° Corner bracket	
 1102 - 1100 Profile, white	 OX - Optiflex lens	 SW - Swivel bracket 180°	
	 OP - Opal lens	<div>Easy beam angle adjustment</div> 	
	 PR - Prime lens		
	 BK - Black lens		
	 OX3D - Square 3D, Optiflex		
	 OP3D - Square 3D, Opal	 3M - Mounting tape, double face	
	 SIL - Silens Serie 1000	 NO - No mounting hardware	
	 NO - No lens		








PROFILE








LENS

MOUNTING HARDWARE

LENGTH

COLOR TEMPERATURE

 24 - 2400K
 27 - 2700K
 30 - 3000K
 35 - 3500K
 42 - 4200K
 53 - 5300K (LHP only)
 62 - 6200K (LP only)

 WD1 - 2200-2700K 14W/m
 WD3 - 2700-3500K 14W/m
 COBWD - 2200-3200K 14W/m
 TW1 - Tunable White 11W/m
 TW2 - Tunable White 19W/m
 RGB1 - RGB 14W/m
 RGB2 - RGB 19W/m
 RGBW2 - 3000K 4in1 14W/m

LUMEN PACKAGE*

LP0 - 119 LM / 1.5W FT / 90+CRI
LP1 - 137 LM / 1.5W FT / 90+CRI
LP2 - 234 LM / 3.0W FT / 90+CRI
LP3 - 335 LM / 4.4W FT / 90+CRI
LP4 - 488 LM / 5.8W FT / 90+CRI
LHP - 668 LM / 7.0W FT / 95+CRI

Lumen Package selection is not available for WD, TW and RGB color options.

LEAD IN/OUT

HW3 - Hardwire 3 FT
HW6 - Hardwire 6 FT
HW9 - Hardwire 9 FT
HWX - Hardwire custom FT
DC3 - DC plug 3 FT
DC6 - DC plug 6 FT
DC9 - DC plug 9 FT
DCX - DC plug custom FT
NO - No lead

USAGE

I - IP22 indoor dry location

For TW or RGB strip options, select either
A [Non-dimming] or
E [Non-dimming DC plug]
in power supply plus the
J [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.

POWER SUPPLY/CONTROL

A - Non-dimming
B - ELV dimming 120V AC
C - ELV dimming 120/277 VAC**
D - 0/10V dimming 120/277 VAC
E - Non-dimming DC plug in
F - DMX
G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W
I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC
J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC
K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC
NO - No driver

*NOTES

*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.

** Only available in 96W - 24V Driver.

TITLE
24

COLOR TEMPERATURE CCT

LUMEN PACKAGE

LEAD IN

LEAD OUT

USAGE

POWER SUPPLY/CONTROL

