


# 1200 PROFILE

1000 Series



## Cross-section dimensions:



## THE STAR OF THE 1000 SERIES

This profile is designed to ensure that the LED source is invisible, offering uniform and soft lighting for the eyes. A compact and versatile luminaire!

### FEATURES

- Designed to give a uniform light without hot spots\* with an opal or prime lens.
- Custom length by sections of 2 to 240 inches (6m).
- Application guide for 10mm (3/8-inch) LED engine or less.
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Compatible with multiple installation accessories.
- Designed to meet North American woodworking standards.
- Conforms to UL STD. 2108 for closet usage.

### OPTIONS



### LED ENGINE COMPATIBILITY

IP22: Compatible with LED engines up to **14mm** wide.


























IP68: Compatible with LED engines up to **10mm** wide.

















### LINEAR WEIGHT

0.099 lbs/ft, 0.148 kg/m (without lens)

\*Dot free only in certain configurations - contact your sales representatives for information



PROFILE	LENSES	MOUNTING HARDWARE	MOTION SENSORS*	LENGTH
 <p><b>1200</b> - 1200 Profile, alu</p>	 <p><b>CL</b> - Clear lens</p>	 <p><b>FL</b> - Flat bracket</p>	 <p><b>SEN1</b> - 30 sec. Embedded</p>	<p>Custom length by sections of 2 to 240 inches (6m).</p>
 <p><b>1201</b> - 1200 Profile, black</p>	 <p><b>SP</b> - Spread lens</p>	 <p><b>45</b> - 45° Corner bracket</p>	 <p><b>SEN2</b> - 30 sec. Outside extrusion</p>	
 <p><b>1202</b> - 1200 Profile, white</p>	 <p><b>OX</b> - Optiflex lens</p>	 <p><b>SW</b> - Swivel bracket 180°</p>	 <p><b>SEN3</b> - 4 min. Embedded</p>	
 <p><b>120X</b> - 1200 Profile, custom color <b>IMPORTANT:</b> Give RAL color No See Appendix 1 on page 266</p>	 <p><b>OP</b> - Opal lens</p>	 <p>Easy beam angle adjustment</p>	 <p><b>SEN4</b> - 4 min. Outside extrusion</p>	
<p>RAL NUMBER</p>	 <p><b>PR</b> - Prime lens</p>	 <p><b>3M</b> - Mounting tape, double face</p>	 <p><b>SEN5</b> - Intergrated proximity hand motion sensor</p>	
	 <p><b>BK</b> - Black lens</p>	 <p><b>NO</b> - No mounting hardware</p>	 <p><b>NO</b> - No sensor</p>	
	 <p><b>FO</b> - Focus lens</p>		<p><b>*NOTES</b></p> <p>All motion sensors: - Max 36W/12V or 72W/24V - Can only be used with non-dimmable power supplies</p>	
	 <p><b>SIL</b> - Silens Serie 1000</p>			
	 <p><b>NO</b> - No lens</p>			
PROFILE	LENS	MOUNTING HARDWARE	MOTION SENSOR	LENGTH

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<ul style="list-style-type: none"> <li> <b>24</b> - 2400K</li> <li> <b>27</b> - 2700K</li> <li> <b>30</b> - 3000K</li> <li> <b>35</b> - 3500K</li> <li> <b>42</b> - 4200K</li> <li> <b>53</b> - 5300K (LHP only)</li> <li> <b>62</b> - 6200K (LP only)</li> <li> <b>WD1</b> - 2200-2700K 14W</li> <li> <b>WD3</b> - 2700-3500K 14W</li> <li> <b>TW1</b> - Tunable White 11W</li> <li> <b>TW2</b> - Tunable White 19W</li> <li> <b>RGB1</b> - RGB 14W</li> <li> <b>RGB2</b> - RGB 19W</li> <li> <b>RGBW1</b> - 3000K</li> <li> <b>RGBW2</b> - 3000K 4in1</li> </ul>	<p><b>LP0</b> - 128 LM / 1.5W FT / 90+CRI</p> <p><b>LP1</b> - 160 LM / 1.5W FT / 90+CRI</p> <p><b>LP2</b> - 255 LM / 3.0W FT / 90+CRI</p> <p><b>LP3</b> - 308 LM / 4.5W FT / 90+CRI</p> <p><b>LP4</b> - 400 LM / 5.8W FT / 90+CRI</p> <p><b>LHP</b> - 700 LM / 7.0W FT / 95+CRI</p> <p><b>Note:</b> Not applicable for Warmdim (WD), Tunable White (TW) &amp; RGB color temperatures</p>	<p><b>HW3</b> - Hardwire 3 FT</p> <p><b>HW6</b> - Hardwire 6 FT</p> <p><b>HW9</b> - Hardwire 9 FT</p> <p><b>HWX</b> - Hardwire custom FT</p> <p><b>DC3</b> - DC plug 3 FT</p> <p><b>DC6</b> - DC plug 6 FT</p> <p><b>DC9</b> - DC plug 9 FT</p> <p><b>DCX</b> - DC plug custom FT</p> <p><b>NO</b> - No lead</p>	<p><b>I</b> - IP22 indoor dry location</p> <p><b>0</b> - IP68 wet/damp location</p> <p><b>Note:</b> IP68 not available with motion sensor option.</p>	<p><b>A</b> - Non-dimming</p> <p><b>B</b> - ELV dimming 120V AC</p> <p><b>C</b> - ELV dimming 120/277 VAC**</p> <p><b>D</b> - 0/10V dimming 120/277 VAC</p> <p><b>E</b> - Non-dimming DC plug in</p> <p><b>F</b> - DMX</p> <p><b>G</b> - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</p> <p><b>I</b> - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</p> <p><b>J</b> - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</p> <p><b>K</b> - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</p> <p><b>NO</b> - No driver</p>	<p>*The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>** Only available in 96W - 24V Driver</p> 
COLOR TEMPERATURE CCT	LUMEN PACKAGE	LEAD IN LEAD OUT	USAGE	POWER SUPPLY/CONTROL	