











































PROFILE	LENSES	MOUNTING HARDWARE	CANOPY	OPTION	LENGTH
 <p>1460 - Series 1400, alu</p>	 <p>PR - Prime lens</p>	 <p>PH - Phantom bracket</p>	<p>NOTE: Only available with SUS bracket (suspension)</p> 	 <p>HER - High efficiency reflector</p>	<p>Custom length by sections of 6 to 240 inches (6m).</p>
 <p>1461 - Series 1400, black</p>	 <p>BK - Black lens</p>	 <p>MG - Magnetic kit</p>	<p>Remote driver canopy plate See Appendix 2 on page 266 CR0 - Alu CR1 - Black CR2 - White</p> 	 <p>NO - No option</p>	
 <p>1462 - Series 1400, white</p>	 <p>NO - No lens</p>	 <p>WSB - Surface 2-side bracket</p>	<p>Integrated driver in canopy See Appendix 2 on page 266 CI0 - Alu CI1 - Black CI2 - White</p> 		
 <p>146X - Series 1400, custom color</p> <p>IMPORTANT: Give RAL color No See Appendix 1 on page 266</p>	 <p>Easy beam angle adjustment</p>	 <p>AWS - Surface 90° bracket</p>	 <p>Integrated driver & suspension kit See Appendix 2 on page 266 CIK0 - Alu CIK1 - Black CIK2 - White</p>		
<p>RAL NUMBER</p>		 <p>W45 - Surface 45° bracket</p>	 <p>NO - No canopy</p>		
		 <p>SWI - Interior Swivel bracket 180°</p>	 <p>HDSW - Heavy duty swivel bracket</p>		
		 <p>SUS - 1400 suspension kit</p>	 <p>NO - No mounting hardware</p>		
PROFILE	LENS	MOUNTING HARDWARE	CANOPY	OPTION	LENGTH

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<ul style="list-style-type: none">  24 - 2400K  27 - 2700K  30 - 3000K  35 - 3500K  42 - 4200K  53 - 5300K (LHP only)  62 - 6200K (LP only)  WD1 - 2200-2700K 14W  WD3 - 2700-3500K 14W  TW1 - Tunable White 11W  TW2 - Tunable White 19W  RGB1 - RGB 14W  RGB2 - RGB 19W  RGBW1 - 3000K  RGBW2 - 3000K 4in1 	<p>LP0 - 128 LM / 1.5W FT / 90+CRI LP1 - 160 LM / 1.5W FT / 90+CRI LP2 - 255 LM / 3.0W FT / 90+CRI LP3 - 308 LM / 4.5W FT / 90+CRI LP4 - 400 LM / 5.8W FT / 90+CRI LHP - 700 LM / 7.0W FT / 95+CRI</p> <p>Note: Not applicable for Warmdim (WD), Tunable White (TW) & RGB color temperatures</p>	<p>HW3 - Hardwire 3 FT HW6 - Hardwire 6 FT HW9 - Hardwire 9 FT HWX - Hardwire custom FT DC3 - DC plug 3 FT DC6 - DC plug 6 FT DC9 - DC plug 9 FT DCX - DC plug custom FT SUS - Coaxial wire 15 FT NO - No lead</p>	<p>I - IP22 indoor dry location 0 - IP68 wet/damp location</p> <p>Note: IP68 not available with motion sensor option.</p>	<p>A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver</p>	<p>*The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>** Only available in 96W - 24V Driver</p> 
COLOR TEMPERATURE CCT	LUMEN PACKAGE	LEAD IN LEAD OUT	USAGE	POWER SUPPLY/CONTROL	