


3200 PROFILE

3000 Series



Cross-section dimensions:



With its smooth and curved inner surface, the new 3200 recessed profile allows indirect lighting with a hollow effect, regardless of the height at which it is installed. What's new? The possibility of adding endcaps for a neat and elegant finish. The 3200 is ideal for residential or commercial applications that require high efficiency, safe lighting.

FEATURES

- Direct adjustment with standard 1/2 inch gypsum panels and with 5/8 inch gypsum panels.
- Impeccable finish thanks to the grooves that allow the profile to be leveled to the wall surface using joint compound.
- Available in 96 inch (2.43 m) lengths for easy and accurate on-site installation. Optional endcaps, available.
- Equipped with a Prime lens for uniform illumination without light dots and optimal light diffusion.
- 8 mm LED light source: 4.8 W, 9.6 W, and 14.5 W, with 7 color temperatures (2400K to 6200K), IP22; also available in 10 mm width in 14.4 W-RGB.

OPTIONS



LED ENGINE COMPATIBILITY

Compatible with LED engines up to **10mm** wide.




LINEAR WEIGHT



0.330lbs/ft, 0.491kg/m (without lens)







3200 Profile ordering sheet

3000 Series

PROFILE	LENSES	LENGTH
 <p>3200 QTY - Profile</p>	 <p>PR - Prime lens</p>  <p>SIL - SiLens</p>	<p>Available in straight section of 8 feet (96 inches/2.4 m). *Cut on site</p>
<div>3200</div> <p>PROFILE</p>	<div>LENS</div>	<div>96"</div> <p>LENGTH</p>
		<p>X</p> <p>QTY</p>

ENDCAPS	ACCESSORIES
 <p>3200 left endcap</p>	 <p>3200 right endcap</p>
<div>QUANTITY</div>	<div>QUANTITY</div>

ACCESSORIES
 <p>Drywall small head screw (x100)</p>
<div>QUANTITY</div>

JOINERS
 <p>JS - Type A straight joiner</p>
<div>JS</div> <p>JOINER</p>
<p>X</p> <p>QTY</p>
 <p>JH135 - Type A horz. 135° joiner</p>
<div>JH135</div> <p>JOINER</p>
<p>X</p> <p>QTY</p>
 <p>JH90 - Type A horz. 90° joiner</p>
<div>JH90</div> <p>JOINER</p>
<p>X</p> <p>QTY</p>

LED engine will be assembled on site. See Appendix 3 to see how to calculate total ordering length.

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<p>24 - 2400K</p> <p>27 - 2700K</p> <p>30 - 3000K</p> <p>35 - 3500K</p> <p>42 - 4200K</p> <p>53 - 5300K (LHP only)</p> <p>62 - 6200K (LP only)</p>	<p>LP0 - 119 LM / 1.5W FT / 90+CRI</p> <p>LP1 - 137 LM / 1.5W FT / 90+CRI</p> <p>LP2 - 234 LM / 3.0W FT / 90+CRI</p> <p>LP3 - 335 LM / 4.4W FT / 90+CRI</p> <p>LP4 - 488 LM / 5.8W FT / 90+CRI</p> <p>LHP - 668 LM / 7.0W FT / 95+CRI</p>	<p>HW3 - Hardwire 3 FT</p> <p>HW6 - Hardwire 6 FT</p> <p>HW9 - Hardwire 9 FT</p> <p>HWX - Hardwire custom FT</p> <p>NO - No lead</p>	<p>I - IP22 indoor dry location</p>	<p>A - Non-dimming</p> <p>B - ELV dimming 120V AC</p> <p>C - ELV dimming 120/277 VAC**</p> <p>D - 0/10V dimming 120/277 VAC</p> <p>E - Non-dimming DC plug in</p> <p>F - DMX</p> <p>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</p> <p>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</p> <p>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</p> <p>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</p> <p>NO - No driver</p>	<p>Total length of LED engine in inches - See Appendix 3 (page 233) on how to calculate length.</p>
<p>WD1 - 2200-2700K 14W/m</p> <p>WD3 - 2700-3500K 14W/m</p> <p>COBWD - 2200-3200K 14W/m</p> <p>TW1 - Tunable White 11W/m</p> <p>TW2 - Tunable White 19W/m</p> <p>RGB1 - RGB 14W/m</p> <p>RGB2 - RGB 19W/m</p>	<p>Lumen Package selection is not available for WD, TW and RGB color options.</p>	<p>For TW or RGB strip options, select either</p> <p>A [Non-dimming] or</p> <p>E [Non-dimming DC plug] in power supply plus the</p> <p>J [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.</p>			

COLOR TEMPERATURE CCT LUMEN PACKAGE LEAD IN LEAD OUT USAGE POWER SUPPLY/CONTROL LED ENGINE LENGTH

*NOTE: The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors. ** Only available in 96W - 24V Driver

TITLE 24