


4400 PROFILE

4000 Series



Cross-section dimensions:



ONE OF THE SMALLEST ON THE MARKET

Guaranteed to be discreet! The 4400 profile is reduced to a minimum with its size of less than half an inch, while accepting a good range of LED engines¹.

(1) Accepts LED engines up to 8mm wide.

FEATURES

- Ultra-compact aluminum profile – 12.2mm wide by 12.2mm high (0.5 x 0.5in).
- Custom length by sections of 2 to 240 inches (6m).
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Designed to meet North American woodworking standards.

LED STRIP COMPATIBILITY

Compatible with LED strips up to **8mm** wide.








LINEAR WEIGHT

0.108 lbs/ft, 0.160 kg/m









4400 Profile ordering sheet

4000 Series

PROFILE	LENSES	MOUNTING HARDWARE	LENGTH
 4400 - 4400 Profile, alu	 CL - Clear lens	 FL - Flat bracket	Custom length by sections of 2 to 240 inches (6m).
 4401 - 4400 Profile, black	 OX - Optiflex lens	 NO - No mounting hardware	
 440X - 4400 Profile, custom color IMPORTANT: Give RAL color No See Appendix 1 on page 256	 OP - Opal lens		
RAL NUMBER	 SIL - SiLens		
	 BK - Black lens		
	 NO - No lens		

PROFILE LENS MOUNTING HARDWARE LENGTH

COLOR TEMPERATURE

	24 - 2400K
	27 - 2700K
	30 - 3000K
	35 - 3500K
	42 - 4200K
	53 - 5300K

LUMEN PACKAGE*

LP0 - 119 LM / 1.5W FT / 90+CRI
LP1 - 137 LM / 1.5W FT / 90+CRI
LP2 - 234 LM / 3.0W FT / 90+CRI
LP3 - 335 LM / 4.4W FT / 90+CRI

LEAD IN/OUT

HW3 - Hardwire 3 FT
HW6 - Hardwire 6 FT
HW9 - Hardwire 9 FT
HWX - Hardwire custom FT
DC3 - DC plug 3 FT
DC6 - DC plug 6 FT
DC9 - DC plug 9 FT
DCX - DC plug custom FT
NO - No lead

USAGE

I - IP22 indoor dry location

POWER SUPPLY/CONTROL

A - Non-dimming
B - ELV dimming 120V AC
C - ELV dimming 120/277 VAC**
D - 0/10V dimming 120/277 VAC
E - Non-dimming DC plug in
F - DMX
G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W
I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC
J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC
K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC
NO - No driver

*NOTES

*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.

** Only available in 96W - 24V Driver



COLOR TEMPERATURE CCT

LUMEN PACKAGE

LEAD IN LEAD OUT

USAGE

POWER SUPPLY/CONTROL