


4400 PROFILE

4000 Series



Cross-section dimensions:



ONE OF THE SMALLEST ON THE MARKET


Guaranteed to be discreet! The 4400 profile is reduced to a minimum with its size of less than half an inch, while accepting a good range of LED engines¹.

(1) Accepts LED engines up to 8mm wide.

FEATURES

- Ultra-compact aluminum profile – 12.2mm wide by 12.2mm high (0.5 x 0.5in).
- Custom length by sections of 2 to 240 inches (6m).
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Compatible with multiple installation accessories.
- Designed to meet North American woodworking standards.
- Conforms to UL STD. 2108 for closet usage.

OPTIONS















LED STRIP COMPATIBILITY








Compatible with LED strips up to **8mm** wide.

LINEAR WEIGHT

0.108 lbs/ft, 0.160 kg/m



PROFILE	LENSES	MOUNTING HARDWARE	LENGTH
 4400 - 4400 Profile, alu	 CL - Clear lens	 FL - Flat bracket	Custom length by sections of 2 to 240 inches (6m).
 4401 - 4400 Profile, black	 OX - Optiflex lens	 NO - No mounting hardware	
 440X - 4400 Profile, custom color IMPORTANT: Give RAL color No. See Appendix 1 on page 266	 OP - Opal lens		
RAL NUMBER	 SIL - SiLens		
	 BK - Black lens		
	 NO - No lens		
PROFILE	LENS	MOUNTING HARDWARE	LENGTH

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
 24 - 2400K  27 - 2700K  30 - 3000K  35 - 3500K  42 - 4200K  53 - 5300K	LP0 - 128 LM / 1.5W FT / 90+CRI LP1 - 160 LM / 1.5W FT / 90+CRI LP2 - 255 LM / 3.0W FT / 90+CRI LP3 - 308 LM / 4.5W FT / 90+CRI	HW3 - Hardwire 3 FT HW6 - Hardwire 6 FT HW9 - Hardwire 9 FT HWX - Hardwire custom FT DC3 - DC plug 3 FT DC6 - DC plug 6 FT DC9 - DC plug 9 FT DCX - DC plug custom FT NO - No lead	I - IP22 indoor dry location	A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver	*The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors. ** Only available in 96W - 24V Driver 
COLOR TEMPERATURE CCT	LUMEN PACKAGE	LEAD IN LEAD OUT	USAGE	POWER SUPPLY/CONTROL	