


4450 PROFILE

4000 Series



Cross-section dimensions:



An extremely small aluminum channel that gives you a linear pin of light to create a beautiful modern look. The extra slim channel can be recessed or surface mounted for the desired effect. This profile is easily installed with a specially designed bracket that snaps into place.

FEATURES

- Ultra-compact aluminum profile
- 0.48" (12.2mm) wide by 0.62" (15.81mm) high
- Custom length by sections of 2 to 240 inches (6m)
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation
- Snap-in bracket for easy installation
- Indoor applications
- Compatible with LED strips up to 8mm wide








LED STRIP COMPATIBILITY

Compatible with LED strips up to **8mm** wide.

LINEAR WEIGHT

0.074 lbs/ft, 0.110 kg/m



PROFILE	LENSES	MOUNTING HARDWARE	GROOVE*	LENGTH
 <p>4450 - 4450 Profile, atu</p>	 <p>PRE - Prime lens edge-to-edge</p>  <p>OPE - Opal lens edge-to-edge</p>  <p>SIL Silicone lens available in continuous run of up to 10m (32ft 9.6in)</p> <p>NO - No lens</p>	 <p>MR - Mounting rail</p> <p>NO - No mounting hardware</p>	 <p>G4450-1/2 - Groove 1/2", 4'</p>  <p>G4450-5/8 - Groove 5/8", 4'</p> <p>NO - No groove</p>	<p>Custom length by sections of 2 to 240 inches (6m).</p> <p>QUANTITY</p> <p>*NOTES</p> <ul style="list-style-type: none"> - Can be used with MR mounting rail - For custom orders of 8' long sections contact your representative



COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<p>24 - 2400K</p> <p>27 - 2700K</p> <p>30 - 3000K</p> <p>35 - 3500K</p> <p>42 - 4200K</p> <p>53 - 5300K</p>	<p>LP0 - 119 LM / 1.5W FT / 90+CRI</p> <p>LP1 - 137 LM / 1.5W FT / 90+CRI</p> <p>LP2 - 234 LM / 3.0W FT / 90+CRI</p> <p>LP3 - 335 LM / 4.4W FT / 90+CRI</p>	<p>HW3 - Hardwire 3 FT</p> <p>HW6 - Hardwire 6 FT</p> <p>HW9 - Hardwire 9 FT</p> <p>HWX - Hardwire custom FT</p> <p>DC3 - DC plug 3 FT</p> <p>DC6 - DC plug 6 FT</p> <p>DC9 - DC plug 9 FT</p> <p>DCX - DC plug custom FT</p> <p>NO - No lead</p>	<p>I - IP22 indoor dry location</p>	<p>A - Non-dimming</p> <p>B - ELV dimming 120V AC</p> <p>C - ELV dimming 120/277 VAC**</p> <p>D - 0/10V dimming 120/277 VAC</p> <p>E - Non-dimming DC plug in</p> <p>F - DMX</p> <p>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</p> <p>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</p> <p>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</p> <p>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</p> <p>NO - No driver</p>	<p>*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>** Only available in 96W - 24V Driver</p> 