


# 5560 PROFILE

5000 Series



## Cross-section dimensions:



## INSTALLS ON CURVED OR UNEVEN SURFACES!

The 5560 profile allows integrating linear LED lighting on **curved or uneven surfaces**. Its low profile (1/5" including lens), and a thickness of less than 1/32" (0.75mm), allows for **effortless bending and installation** using plain mounting tape.

### FEATURES

- Custom length by sections of 96 inches (2.44m).
- Thin, lightweight and flexible, can be easily bent over curved or uneven surfaces.
- Can be installed using adhesives/mounting tape.
- Made of ALCOA 6063-T5 aluminum alloy, increasing heat dissipation and the lifetime of your LED engine.
- Designed to meet North American woodworking standards.

### OPTIONS



### LED ENGINE COMPATIBILITY

Compatible with LED engines up to **12mm** wide.






### LINEAR WEIGHT

0.033 lbs/ft, 0.049 kg/m (without lens)



# 5560 Profile ordering sheet

## 5000 Series

PROFILE	LENSES	MOUNTING HARDWARE	LENGTH	IMPORTANT NOTES
 5560 - 5560 Profile, alu	 OP - Opal lens   NO - No lens	 3M - Mounting tape, double face   NO - No mounting hardware	Custom length by sections of 2 to 96 inches (2.44m).	Due to installation specifics, LED tape is shipped separately and must be installed on site by the client after all bending and shaping is complete.  There is no endcap for this series.
5560	-	-	-	
PROFILE	LENS	MOUNTING HARDWARE	LENGTH	

5000

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<div>24 - 2400K</div> <div>27 - 2700K</div> <div>30 - 3000K</div> <div>35 - 3500K</div> <div>42 - 4200K</div> <div>53 - 5300K (LHP only)</div> <div>62 - 6200K (LP only)</div> <div>WD1 - 2200-2700K 14W</div> <div>WD3 - 2700-3500K 14W</div> <div>TW1 - Tunable White 11W</div> <div>TW2 - Tunable White 19W</div> <div>RGB1 - RGB 14W</div> <div>RGB2 - RGB 19W</div>	<div>LP0 - 119 LM / 1.5W FT / 90+CRI</div> <div>LP1 - 137 LM / 1.5W FT / 90+CRI</div> <div>LP2 - 234 LM / 3.0W FT / 90+CRI</div> <div>LP3 - 335 LM / 4.4W FT / 90+CRI</div> <div>LP4 - 488 LM / 5.8W FT / 90+CRI</div> <div>LHP - 668 LM / 7.0W FT / 95+CRI</div> <div>Lumen Package selection is not available for <b>WD, TW</b> and <b>RGB</b> color options.</div>	<div>HW3 - Hardwire 3 FT</div> <div>HW6 - Hardwire 6 FT</div> <div>HW9 - Hardwire 9 FT</div> <div>HWX - Hardwire custom FT</div> <div>DC3 - DC plug 3 FT</div> <div>DC6 - DC plug 6 FT</div> <div>DC9 - DC plug 9 FT</div> <div>DCX - DC plug custom FT</div> <div>NO - No lead</div>	<div>I - IP22 indoor dry location</div> <div>For <b>TW</b> or <b>RGB</b> strip options, select either  <b>A</b> [Non-dimming] or  <b>E</b> [Non-dimming DC plug] in power supply plus the  <b>J</b> [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.</div>	<div>A - Non-dimming</div> <div>B - ELV dimming 120V AC</div> <div>C - ELV dimming 120/277 VAC**</div> <div>D - 0/10V dimming 120/277 VAC</div> <div>E - Non-dimming DC plug in</div> <div>F - DMX</div> <div>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</div> <div>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</div> <div>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</div> <div>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</div> <div>NO - No driver</div>	<div>*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.</div> <div>** Only available in 96W - 24V Driver.</div>
COLOR TEMPERATURE CCT	LUMEN PACKAGE	LEAD IN	LEAD OUT	USAGE	POWER SUPPLY/CONTROL