


# 5560 PROFILE

5000 Series



## Cross-section dimensions:



## INSTALLS ON CURVED OR UNEVEN SURFACES!

The 5560 profile allows integrating linear LED lighting on **curved or uneven surfaces**. Its low profile (1/5" including lens), and a thickness of less than 1/32" (0.75mm), allows for **effortless bending and installation** using plain mounting tape.

### FEATURES

- Sold in straight sections of 8' (2.44m).
- Thin, lightweight and flexible, can be easily bent over curved or uneven surfaces.
- Can be installed using adhesives/mounting tape.
- Made of ALCOA 6063-T5 aluminum alloy, increasing heat dissipation and the lifetime of your LED engine.
- Designed to meet North American woodworking standards.

### OPTIONS



### LED ENGINE COMPATIBILITY

Compatible with LED engines up to **12mm** wide.






### LINEAR WEIGHT

0.033 lbs/ft, 0.049 kg/m (without lens)



# 5560 Profile ordering sheet

## 5000 Series

| PROFILE   | LENSES   | MOUNTING HARDWARE  | LENGTH  | IMPORTANT NOTES   |
|---|--|--|---|---|
| <br>5560 - 5560 Profile, alu | <br>OP - Opal lens<br><br><br>NO - No lens | <br>3M - Mounting tape, double face<br><br><br>NO - No mounting hardware | Available in straight section of 8 feet (96 inches/2.4 m).<br><br>96" X | Due to installation specifics, LED tape is shipped separately and must be installed on site by the client after all bending and shaping is complete.<br><br>There is no endcap for this series. |
| 5560  | -  | -  | 96"   | X   |
| PROFILE   | LENS   | MOUNTING HARDWARE  | LENGTH  | QTY   |

5000

### COLOR TEMPERATURE

- 24 - 2400K
- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 42 - 4200K
- 53 - 5300K (LHP only)
- 62 - 6200K (LP only)

- WD1 - 2200-2700K 14W/m
- WD3 - 2700-3500K 14W/m
- COBWD - 2200-3200K 14W/m
- TW1 - Tunable White 11W/m
- TW2 - Tunable White 19W/m
- RGB1 - RGB 14W/m
- RGB2 - RGB 19W/m

### LUMEN PACKAGE\*

- LP0 - 119 LM / 1.5W FT / 90+CRI
- LP1 - 137 LM / 1.5W FT / 90+CRI
- LP2 - 234 LM / 3.0W FT / 90+CRI
- LP3 - 335 LM / 4.4W FT / 90+CRI
- LP4 - 488 LM / 5.8W FT / 90+CRI
- LHP - 668 LM / 7.0W FT / 95+CRI

Lumen Package selection is not available for WD, TW and RGB color options.

### LEAD IN/OUT

- HW3 - Hardwire 3 FT
- HW6 - Hardwire 6 FT
- HW9 - Hardwire 9 FT
- HWX - Hardwire custom FT
- DC3\*\* - DC plug 3 FT
- DC6\*\* - DC plug 6 FT
- DC9\*\* - DC plug 9 FT
- DCX\*\* - DC plug custom FT
- NO - No lead

### USAGE

- I - IP22 indoor dry location

For TW or RGB strip options, select either  
A [Non-dimming] or  
E [Non-dimming DC plug]  
in power supply plus the  
J [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.

### POWER SUPPLY/CONTROL

- A - Non-dimming
- B - ELV dimming 120V AC
- C - ELV dimming 120/277 VAC\*\*\*
- D - 0/10V dimming 120/277 VAC
- E - Non-dimming DC plug in
- F - DMX
- G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W
- I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC
- J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC
- K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC
- NO - No driver

### \*NOTES

\*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.

\*\* Only available for static white and Warm Dim options

\*\*\* Only available in 96W - 24V Driver.

TITLE  
24  
COMPLIANT

COLOR TEMPERATURE CCT

LUMEN PACKAGE

LEAD IN

LEAD OUT

USAGE

POWER SUPPLY/CONTROL

