


# 7500 PROFILE

7000 Series



## Cross-section dimensions:



This 7500 series has direct, indirect or combined lighting options. Combining style and **elegance in a beautiful round format**, the 7500 profile is designed to be a suspended fixture with different and independent lumen package for both lighting options to achieve a wide variety of looks and lighting effects. This charming light fixture, is perfect for your project in either residential or commercial applications.

## FEATURES

- Customizable lengths by sections from 2 to 240 inches (6m).
- Designed to give a uniform light without hot spots with a prime lens\*.
- Large variety of optics allows for greater creativity.
- 2 different suspension options; fixed and pivoting.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Increases the practical life of your LEDs with better heat dissipation.
- Designed to meet North American woodworking standards.

\*Dot free only in certain configurations - contact your sales representatives for information

## OPTIONS























## LED ENGINE COMPATIBILITY

Compatible with LED engines up to **12mm** wide.

## LINEAR WEIGHT

0.433 lbs/ft, 0.644 kg/m (without lens)



PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	CANOPY	LENGTH
 <p>7500 - 7500 Profile, alu</p>	 <p>OX - Optiflex lens</p>	 <p>CL - Clear lens</p>	 <p>SUS - Suspension kit with 15ft. aircraft cable</p>	<p><b>NOTE:</b> Only available with <b>SUS</b> bracket (suspension)</p>  <p>Remote driver canopy plate See Appendix 2 on page 262 CR0 - Alu CR1 - Black CR2 - White</p>	<p>Custom length by sections of 2 to 96"</p> <p>Swivel maximum length = 72"</p>
 <p>7501 - 7500 Profile, black</p>	 <p>PR - Prime lens</p>	 <p>SP - Spread lens</p>	 <p>Suspension swivel kit with 15ft. aircraft cable</p>	 <p>Integrated driver in canopy See Appendix 2 on page 262 C10 - Alu C11 - Black C12 - White</p>	
 <p>7502 - 7500 Profile, white</p>	 <p>NO - No lens</p>	 <p>OX - Optiflex lens</p>	 <p>SWRD - Red loop</p>	 <p>Integrated driver &amp; suspension kit See Appendix 2 on page 262 C1K0 - Alu C1K1 - Black C1K2 - White</p>	
 <p>750X - 7500 Profile, custom color</p> <p><b>IMPORTANT:</b> Give RAL color No See Appendix 1 on page 262</p>	 <p>NO - No lens</p>	 <p>OP - Opal lens</p>	 <p>SWPK - Pink loop</p>	 <p>NO - No canopy</p>	
<p>RAL NUMBER</p>					
PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	CANOPY	LENGTH

COLOR TEMPERATURE	LM PACKAGE DOWN/UP*	POWER CABLE FINISH	USAGE	POWERSUPPLY/CONTROL**	*NOTES
<p>24 - 2400K</p> <p>27 - 2700K</p> <p>30 - 3000K</p> <p>35 - 3500K</p> <p>42 - 4200K</p> <p>53 - 5300K (LHP only)</p> <p>62 - 6200K (LP only)</p> <p>WD1 - 2200-2700K 14W</p> <p>WD3 - 2700-3500K 14W</p> <p>TW1 - Tunable White 11W</p> <p>TW2 - Tunable White 19W</p> <p>RGB1 - RGB 14W</p> <p>RGB2 - RGB 19W</p> <p>RGBW1 - 3000K</p> <p>RGBW2 - 3000K 4in1</p> <p>NO - No up light (w/ opal lens)</p>	<p>LP0 - 128 LM / 1.5W FT / 90+CRI</p> <p>LP1 - 160 LM / 1.5W FT / 90+CRI</p> <p>LP2 - 255 LM / 3.0W FT / 90+CRI</p> <p>LP3 - 308 LM / 4.5W FT / 90+CRI</p> <p>LP4 - 400 LM / 5.8W FT / 90+CRI</p> <p>LHP - 700 LM / 7.0W FT / 95+CRI</p> <p>NO - No up light (w/ opal lens)</p> <p><b>Note:</b> Not applicable for Warmdim (WD), Tunable White (TW) &amp; RGB color temperatures</p>	<p>BK - Black</p> <p>WH - White</p> <p>RD - Red</p> <p>BC - Black/White Chevron</p>	<p>I - IP22 indoor dry location</p>	<p>A - Non-dimming</p> <p>B - ELV dimming 120V AC</p> <p>C - ELV dimming 120/277 VAC***</p> <p>D - 0/10V dimming 120/277 VAC</p> <p>E - Non-dimming DC plug in</p> <p>F - DMX</p> <p>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</p> <p>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</p> <p>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</p> <p>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</p> <p>NO - No driver</p>	<p>* The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and transluency conversion factors.</p> <p>** By default both Up &amp; Down LED engines are controlled from one source. For custom options, please contact your local representative.</p> <p>***Only available in 96W - 24W Driver</p>
CCT DOWN	CCT UP	LM DOWN	LM UP	POWER CABLE FINISH	USAGE

# NOTES

