


7500 PROFILE

7000 Series



Cross-section dimensions:



This 7500 series has direct, indirect or combined lighting options. Combining style and **elegance in a beautiful round format**, the 7500 profile is designed to be a suspended fixture with different and independent lumen package for both lighting options to achieve a wide variety of looks and lighting effects. This charming light fixture, is perfect for your project in either residential or commercial applications.

FEATURES

- Customizable lengths by sections from 2 to 240 inches (6m).
- Designed to give a uniform light without hot spots with a prime lens*.
- Large variety of optics allows for greater creativity.
- 2 different suspension options; fixed and pivoting.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Increases the practical life of your LEDs with better heat dissipation.
- Designed to meet North American woodworking standards.

OPTIONS



LED ENGINE COMPATIBILITY

Compatible with LED engines up to **12mm** wide.

LINEAR WEIGHT



















0.433 lbs/ft, 0.644 kg/m (without lens)

*Dot free only in certain configurations - contact your sales representatives for information



7500 Profile ordering sheet

7000 Series

PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	SUSPENSION / RECESS	LENGTH
 7500 - 7500 Profile, alu	 OX - Optiflex lens	 CL - Clear lens	 SUS - Suspension kit with 15ft. aircraft cable	 Canopy plate See Appendix 2 on page 254 CR0 - Alu CR1 - Black CR2 - White	Custom length by sections of 2 to 240" Swivel maximum length = 72"
 7501 - 7500 Profile, black	 PR - Prime lens	 SP - Spread lens	 Suspension swivel kit with 15ft. aircraft cable SWRD - Red loop SWPK - Pink loop SWCY - Cyan loop SWBK - Black loop SWBL - Blue loop SWWH - White loop SWGR - Green loop SWTR - Transparent loop SWOR - Orange loop	 Integrated junction box in canopy See Appendix 2 on page 254 CI0 - Alu CI1 - Black CI2 - White	
 7502 - 7500 Profile, white	 NO - No lens	 OX - Optiflex lens		 Integrated junction box & suspension kit See Appendix 2 on page 254 CIK0 - Alu CIK1 - Black CIK2 - White	
 750X - 7500 Profile, custom color IMPORTANT: Give RAL color No See Appendix 1 on page 254	 NO - No lens	 PR - Prime lens		 NO - No canopy	
RAL NUMBER					

PROFILE LENS DOWN LENS UP MOUNTING HARDWARE CANOPY LENGTH

7000

COLOR TEMPERATURE	LUMEN PACKAGE*	POWER CABLE FINISH	USAGE	POWER SUPPLY/CONTROL	*NOTES
24 - 2400K 27 - 2700K 30 - 3000K 35 - 3500K 42 - 4200K 53 - 5300K (LHP only) 62 - 6200K (LP only)	LP0 - 119 LM / 1.5W FT / 90+CRI LP1 - 137 LM / 1.5W FT / 90+CRI LP2 - 234 LM / 3.0W FT / 90+CRI LP3 - 335 LM / 4.4W FT / 90+CRI LP4 - 488 LM / 5.8W FT / 90+CRI LHP - 668 LM / 7.0W FT / 95+CRI NO - No up light (w/ opal lens)	BK - Black WH - White RD - Red BC - Black/White Chevron	I - IP22 indoor dry location For TW or RGB strip options, select either A [Non-dimming] or E [Non-dimming DC plug] in power supply plus the J [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.	A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver	*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors. ** By default both Up & Down LED engines are controlled from one source. For custom options, please contact your local representative. ***Only available in 96W - 24W Driver
WD1 - 2200-2700K 14W WD3 - 2700-3500K 14W TW1 - Tunable White 11W TW2 - Tunable White 19W RGB1 - RGB 14W RGB2 - RGB 19W RGBW2 - 3000K 4in1 NO - No up light (opal lens)	Lumen Package selection is not available for WD , TW and RGB color options.				
CCT DOWN CCT UP LM DOWN LM UP POWER CABLE FINISH USAGE POWER SUPPLY/CONTROL					