


# 7650 PROFILE (TUBE)

VERTICAL SUSPENSION

7000 Series



Cross-section dimensions:



A stunning vertically mounted linear tubular pendant luminaire designed to create a timeless effect in lobbies, stairwells, and entrances. Offering a seamless 360 degrees of illumination with a 4-sided heatsink that preserves the life of LED chips. This custom decorative luminaire is available in lengths up to 4 feet. It is offered in a wide range of color temperatures and light outputs, allowing you to vary the intensity, and color of the light. The suspended fixture is powered with a remote driver. The acrylic tube delivers a beautiful custom decorative luminaire.

## FEATURES

- Custom length by sections of 6 to 48 inches (1.22m)
- 4-sided heat sink
- Vertical suspension mounting over the power cable
- Uniform 360° of light without hot spots
- Acrylic lens for high-performance optics



## OPTIONS




## LINEAR WEIGHT

0.529 lbs/ft, 0.787 kg/m (acrylic tube with Aluminum heat sink insert only)



LUMINAIRE	POWER CABLE FINISH	CANOPY	LENGTH
 <p>7650V - Acrylic diffuser tube luminaire, vertical suspension</p>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: black; margin-right: 5px;"></span> BK - Black</li> <li><span style="display: inline-block; width: 15px; height: 10px; border: 1px solid black; margin-right: 5px;"></span> WH - White</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: red; margin-right: 5px;"></span> RD - Red</li> <li><span style="display: inline-block; width: 15px; height: 10px; border: 1px dashed black; margin-right: 5px;"></span> BC - Black/White Chevron</li> </ul>	 <p>Remote driver round canopy 5 1/4" x 1"</p> <ul style="list-style-type: none"> <li>CR0 - Alu</li> <li>CR1 - Black</li> <li>CR2 - White</li> </ul>	<p>Custom length 6" - 48"</p>
<b>7650V</b>			
LUMINAIRE	POWER CABLE FINISH	CANOPY	LENGTH

7000

COLOR TEMPERATURE	LUMEN PACKAGE*	USAGE	POWER SUPPLY/CONTROL	*NOTES
<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4a460; margin-right: 5px;"></span> 24 - 2400K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f08080; margin-right: 5px;"></span> 27 - 2700K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f0e68c; margin-right: 5px;"></span> 30 - 3000K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f0e68c; margin-right: 5px;"></span> 35 - 3500K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f0e68c; margin-right: 5px;"></span> 42 - 4200K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f0e68c; margin-right: 5px;"></span> 62 - 6200K</li> </ul>	<ul style="list-style-type: none"> <li>4LP1 - 548 LM / 6.0W FT / 90+CRI</li> <li>4LP2 - 936 LM / 12.0W FT / 90+CRI</li> <li>4LP3 - 1340 LM / 17.6W FT / 90+CRI</li> </ul>	<p>I - IP22 indoor dry location</p>	<ul style="list-style-type: none"> <li>A - Non-dimming</li> <li>B - ELV dimming 120V AC</li> <li>C - ELV dimming 120/277 VAC**</li> <li>D - 0/10V dimming 120/277 VAC</li> <li>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</li> <li>NO - No power supply</li> </ul>	<p>*The light output is provided in lumens per foot, for a CCT of 4200K without lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>**Only available in 96W - 24W power supply.</p>
<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4a460; margin-right: 5px;"></span> WD1 - 2200-2700K 14W</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f08080; margin-right: 5px;"></span> WD3 - 2700-3500K 14W</li> </ul>		<b>I</b>		
COLOR TEMPERATURE CCT	LUMEN PACKAGE	USAGE	POWER SUPPLY/CONTROL	