


9400 PROFILE

9000 Series



Cross-section dimensions:



The **9400 profile** with its twin mounting channels allows for a **wide range of installation options**. Whether on swivel arms, on a surface, or suspended, it can be built in complex spatial configurations using **corner joiners**. Its rugged build in 6063-T5 aluminum alloy will withstand abuse in demanding applications and extreme weather, all of it with an understated elegance.

FEATURES

- The ALCOA 6063-T5 aluminum alloy increases heat dissipation, for an extended lifetime of the LED source, and is suitable for outdoor installation.
- Custom length by sections of 2 to 240 inches (6m).
- 3 position slots for the LED heat sink insert for setting the needed beam angle.
- Accepts multiple or oversized LED sources on a 33mm (1.25in) wide area, for extra power. Has 3 application guides for 10mm (3/8-inch) wide LED engines.
- Designed to give a uniform light without hot spots.
- Its mounting channels make it compatible with a wide range of installation accessories.

OPTIONS




LED ENGINE COMPATIBILITY

Compatible with LED engines and PCBs up to **33mm** wide.


















LINEAR WEIGHT
















0.697 lbs/ft, 1.038 kg/m (without lens or insert)



9400 Profile ordering sheet

9000 Series

PROFILE	LENSES	MOUNTING HARDWARE	CANOPY	OPTION	LENGTH
 <p>9400 - Profile, Alu</p>  <p>9401 - Profile, Black</p>  <p>9402 - Profile, White</p>  <p>940X - 9400 Profile, custom color</p> <p>IMPORTANT: Give RAL color № See Appendix 1 on page 260</p> <p>RAL NUMBER</p>  <p>9400 corner 90°, 6x6" Joiners to be ordered separately</p> <p>CH900 - 9400 corner 90°, 6x6", alu</p> <p>CH901 - 9400 corner 90°, 6x6", black</p> <p>CH902 - 9400 corner 90°, 6x6", white</p>  <p>9400 corner 135°, 6x6" Joiners to be ordered separately</p> <p>CH1350 - 9400 corner 135°, 6x6", alu</p>  <p>Joiners</p> <p>JS - Type B straight joiner</p>	 <p>CL - Clear lens</p>  <p>OX - Optiflex lens</p>  <p>OP - Opal Lens</p>  <p>PR - Prime Lens</p>  <p>FO - Focus lens</p> <p>NO - No lens</p>	 <p>CLIP - Clip-in Bracket</p> <p>Surface 2-side bracket</p> <p>S20 - Alu S21 - Black S22 - White</p> <p>Surface 1-side bracket</p> <p>S10 - Alu S11 - Black S12 - White</p> <p>Surface 90-deg. bracket</p> <p>S30 - Alu S31 - Black S32 - White</p> <p>Swivel wall bracket</p> <p>SW0 - Alu SW1 - Black SW2 - White</p> <p>Swivel sign arm, 6" offset</p> <p>SA60 - Alu SA61 - Black SA62 - White</p> <p>Swivel sign arm, 18" offset</p> <p>SA180 - Alu SA181 - Black SA182 - White</p> <p>Type B dbl. chann. susp. kit with 15ft. aircraft cable</p> <p>SUS0 - Alu SUS1 - Black SUS2 - White</p> <p>NO - No mounting hardware</p>	<p>NOTE: Only available with SUS bracket (suspension)</p>  <p>Remote driver canopy plate See Appendix 2 on page 260</p> <p>CR0 - Alu CR1 - Black CR2 - White</p>  <p>Integrated driver in canopy See Appendix 2 on page 260</p> <p>CI0 - Alu CI1 - Black CI2 - White</p>  <p>Integrated driver & suspension kit See Appendix 2 on page 260</p> <p>CIK0 - Alu CIK1 - Black CIK2 - White</p> <p>NO - No canopy</p>	 <p>HER - High efficiency reflector</p> <p>NO - No option</p>	<p>Custom length by sections of 6 to 240 inches (6m).</p>

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
 24 - 2400K  27 - 2700K  30 - 3000K  35 - 3500K  42 - 4200K  53 - 5300K (LHP only)  62 - 6200K (LP only)  WD1 - 2200-2700K 14W  WD3 - 2700-3500K 14W  TW1 - Tunable White 11W  TW2 - Tunable White 19W  RGB1 - RGB 14W  RGB2 - RGB 19W  RGBW1 - 3000K  RGBW2 - 3000K 4in1	<p>LP0 - 128 LM / 1.5W FT / 90+CRI LP1 - 160 LM / 1.5W FT / 90+CRI LP2 - 255 LM / 3.0W FT / 90+CRI LP3 - 308 LM / 4.5W FT / 90+CRI LP4 - 400 LM / 5.8W FT / 90+CRI LHP - 700 LM / 7.0W FT / 95+CRI</p> <p>Note: Not applicable for Warmdim (WD), Tunable White (TW) & RGB color temperatures</p>	<p>HW3 - Hardwire 3 FT HW6 - Hardwire 6 FT HW9 - Hardwire 9 FT HWX - Hardwire custom FT DC3 - DC plug 3 FT DC6 - DC plug 6 FT DC9 - DC plug 9 FT DCX - DC plug custom FT SUS - Coaxial wire 15 FT NO - No lead</p>	<p>I - IP22 indoor dry location 0 - IP68 wet/damp location</p>	<p>A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI+Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver</p>	<p>* Double strip option cannot be used with the reflector.</p> <p>**The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>*** Only available in 96W - 24V Driver.</p>

SINGLE-STRIP1 DOUBLE-STRIP2* SINGLE STRIP DOUBLE STRIP LEAD IN LEAD OUT USAGE POWER SUPPLY/CONTROL