


LUXSLEEVE PROFILE

PVC Series



Cross-section dimensions:



Looking for mood light without breaking the bank? This PVC extrusion sleeve allows for better light diffusion while being the most economical option for our LuxLine series. Available in 4', you can easily cut it to design ambient light in so many ways. Making dark spaces more inviting has never been so easy.

FEATURES

- Simple and lightweight extrusion made of durable PVC material
- Economical and long lasting
- Two lens options available: Prime or Clear
- Fine grooves on the inner surface of the lens provide even and effective light distribution
- Wide variety of color temperatures available (2400 - 4000K)
- Perfect solution for accent lighting
- Grooves on the extrusion surface provide perfect grip for our LuxLine 120V LED tape
- Easy to cut and install, no mounting brackets required
- Available in straight sections of 4' (1.2m)



LED ENGINE COMPATIBILITY

Compatible with LuxLine 120V LED engines.

LINEAR WEIGHT

0.1 lbs/ft, 0.16 kg/m (with lens)










LUXSLEEVE Profile ordering sheet


PVC Series


LENSES	PROFILE	LENGTH
 <p>LSPR - Prime lens</p>	 <p>LuxSleeve, PVC Series, white</p> <p>INCLUDED</p>	<p>Available in straight section of 4 feet (48 inches/1.2 m). *Cut on site</p>
 <p>LSCL - Clear lens</p>		
LENS	- QUANTITY	X LENGTH
		48 INCHES

IMPORTANT NOTES

LuxSleeve serves as mounting hardware and light diffuser for LuxLine 120V LED tape.

LuxLine (both DIY and overmold options) end cap / connector will always stay outside LuxSleeve (see img.).



COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN	USAGE	NOTES
 <p>24 - 2400K 27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K</p>	LUX - 330 LM / 4.0W FT / 90+CRI	<p>PG - Plug-in 47" HW - Hardwire 118"</p>	2 - IP64 indoor	* The light output is provided in lumens per foot, for a CCT of 4000K and without lens.
COLOR TEMPERATURE CCT	- LUX -	LEAD IN	- IP64 -	
	LUMEN PACKAGE		IP RATING	

- ### LUXLINE FEATURES
- LumenTruss Driverless technology.
 - Direct line voltage.
 - Constant voltage with constant current design providing uniform intensity over the entire run.
 - Uses North American power plug with built-in fuse or hardwire.
 - Order in lengths of 1 FT.
 - 164 FT maximum run.
 - High lumen output.
 - Architectural grade.
 - PVC coating (not recommended for direct sunlight).
 - 3 year warranty.
 - LED type: 3056
 - WARNING: Do not cut AC plug.

