


# TIGA

Wood Series



## Cross-section dimensions:



Go for the warmth of the **natural essence of wood**. Liven up your spaces with our ecological lighting fixtures made of recycled wood from Quebec. The slim **TIGA** will match any décor with its smoothed out sides, and can be combined with a linear canopy for extra style.

## FEATURES

- Made from sustainably harvested and recycled pine hardwood.
- Custom length by sections of 12 to 144 inches (3.6m).
- The insert is made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Designed to give a uniform light without hot spots with a Prime lens.
- Choose from direct or direct/ indirect lighting.
- Suspended pendant with remote driver.
- A natural finish permits client to select and apply their own stain to match the decor.
- Indoor use.
- Revit file available.

## OPTIONS



## LED ENGINE COMPATIBILITY

### Direct (down):

Compatible with LED tapes up to **14mm** wide.









### Indirect (up):

Compatible with LED tapes up to **14mm** wide.

## LINEAR WEIGHT

1.141 lbs/ft, 1.699 kg/m (without lens or insert)



PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	CANOPY	LENGTH
 <p><b>TIGN</b> - Wood enclosure, natural finish Aluminum heat sink included with profiles</p>	 <p><b>PR</b> - Prime lens</p>	 <p><b>CL</b> - Clear lens</p>  <p><b>PR</b> - Prime lens</p>  <p><b>NO</b> - No lens</p>	 <p><b>SUS</b> - Suspension kit with 15ft. aircraft cable</p>	 <p><b>Remote driver canopy plate</b> See Appendix 2 on page 260 <b>CR0</b> - Alu <b>CR1</b> - Black <b>CR2</b> - White</p>  <p><b>NO</b> - No canopy</p>	<p>Custom length by sections of 12 to 144 inches (3.6m), in increments of 12 inches (30cm).</p> <p>By default suspension will be installed 6 inches (15.3cm) from the ends of the profile. For custom options please contact your local representative.</p>

<b>TIGN</b>	-	<b>PR</b>	-	<b>SUS</b>	-	
PROFILE		LENS DOWN		MOUNTING HARDWARE		CANOPY
			LENS UP			LENGTH

COLOR TEMPERATURE		LUMEN PACKAGE*	USAGE	POWER SUPPLY/CONTROL	*NOTES
<div><div></div>24 - 2400K</div> <div><div></div>27 - 2700K</div> <div><div></div>30 - 3000K</div> <div><div></div>35 - 3500K</div> <div><div></div>42 - 4200K</div> <div><div></div>53 - 5300K (LHP only)</div> <div><div></div>62 - 6200K (LP only)</div>	<div>LP0 - 119 LM / 1.5W FT / 90+CRI</div> <div>LP1 - 137 LM / 1.5W FT / 90+CRI</div> <div>LP2 - 234 LM / 3.0W FT / 90+CRI</div> <div>LP3 - 335 LM / 4.4W FT / 90+CRI</div> <div>LP4 - 488 LM / 5.8W FT / 90+CRI</div> <div>LHP - 668 LM / 7.0W FT / 95+CRI</div>	<div>I - IP22 indoor dry location</div>	<div>A - Non-dimming</div> <div>B - ELV dimming 120V AC</div> <div>C - ELV dimming 120/277 VAC**</div> <div>D - 0/10V dimming 120/277 VAC</div> <div>E - Non-dimming DC plug in</div> <div>F - DMX</div> <div>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</div> <div>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</div> <div>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</div> <div>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</div> <div>NO - No driver</div>	<div>* The light output is provided in lumens per foot, for a CCT of 4200K and without lens. Please refer to the optics page for CCT and translucency conversion factors.</div> <div>** By default both Up &amp; Down LED engines are controlled from one source. For custom options, please contact your local representative.</div> <div>*** Only available in 96W - 24V Driver</div>	
<div><div></div>WD1 - 2200-2700K 14W/m</div> <div><div></div>WD3 - 2700-3500K 14W/m</div> <div><div></div>COBWD - 2200-3200K 14W/m</div> <div><div></div>TW1 - Tunable White 11W/m</div> <div><div></div>TW2 - Tunable White 19W/m</div> <div><div></div>RGB1 - RGB 14W/m</div> <div><div></div>RGB2 - RGB 19W/m</div> <div><div></div>RGBW2 - 3000K 4in1 14W/m</div> <div><div></div>NO - No up light (opal lens)</div>	<div>Lumen Package selection is not available for <b>WD</b>, <b>TW</b> and <b>RGB</b> color options.</div>	<div>For <b>TW</b> or <b>RGB</b> strip options, select either</div> <div><div>A</div>[Non-dimming] or</div> <div><div>E</div>[Non-dimming DC plug] in power supply plus the</div> <div><div>J</div>[Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.</div>			
CCT DOWN	CCT UP	LM DOWN	LM UP	USAGE	POWER SUPPLY/CONTROL

TITLE

24

WALLWASH